

# 4.5" Radiance™ LED Overhead Light



## Features

- Air flow vents added to dissipate heat
- Polycarbonate lens provides the appearance of frosted glass while offering maximum light output and a soft diffused glow
- Available with or without an integral on/off switch
- Color control technology guarantees the color difference between lights is undetectable to the human eye
- RGB(W) option contains a lockout circuit to prevent the white and RGB LEDs from being on at the same time

## Product Details

Mounting	Surface		Recessed	
Lens Material	Polycarbonate		Polycarbonate	
Voltage	13.6V DC		13.6V DC	
Wattage	Std: 3.8W High: 3.9W	3.5W	3.8W	3.3W
Current	Std: 0.28A High: 0.29A	0.3A	0.32A	0.24A
Lumens	Std: 255LM High: 335LM	315LM	250LM	285LM
Color Temp.	3000K, 3500K or 4000K	RGB/3000K, RGB/3500K, or RGB/4000K	3000K or 4000K	RGB/3000K, RGB/3500K, or RGB/4000K
Cutout	N/A		3.5"	
Listing	CSA		CSA	

## Specification Guide

Sample Part #: 69253CUSM-03-0030



### 4.5" Surface Mount Radiance

Base Part #	Switch Option	Mounting Style	Type of LEDs	Color Temp.
69253C	U - Unswitched S - Switched*	SM - Surface Mount	03 - Standard* 04 - High	0030 - 3000K 0035 - 3500K 0040 - 4000K
				RGB30 - RGB/3000K RGB/35 - RGB/3500K RGB40 - RGB/4000K

\*Applies to single color only

### 4.5" Recessed Radiance

Base Part #	Mounting Style	Type of LEDs	Color Temp.
69240PC	NS - Screw Mount -Leave blank for spring mount	15 - Standard	3KE - 3000K 4KE - 4000K
	SP - Spring Mount NS - Screw Mount		RGB30 - RGB/3000K RGB35 - RGB/3500K RGB40 - RGB/4000K

