

Frontier™ Curve

Integrated LED Backlit Mirror



Features

- Rounded corners for a more modern, updated look
- Outer frosted etching provides a soft glow, enhancing the look of the mirror
- Copper-free backing for greater corrosion and scratch resistance
- Power supply available in 0-10V or line voltage dimming
- Various size and color options available (contact sales for stock)

Specification Guide

Sample Part #: 694EM2436-30SO00B


Base Part #
 Size
 Color Temperature
 Output

Base Part #	Size	Color Temp.	Output
694EM	2436 - 24"W x 36"L	30 - 3000K	SO00B - Standard

*Power Supplies are ordered separately

Product Details

Part #'s	694EM2436-KKSO00B	690010.121 - 0-10V Dimming 690010.143 - Line Voltage
Dimensions	24"W x 36"H x 1.7"D	13"L x 1.25"W x 1.7"D
Housing	Anodized Aluminum	Aluminum
Lens	Glass	N/A
Wattage	30W	96W
Voltage	24V DC	120 - 277V AC
Current	1.3A	Max 4A
Lumens	2500LM @ 3500K	N/A
Kelvin	3000K	N/A
Power Factor	N/A	0.94 @ 120V AC
Frequency	N/A	50 - 60Hz



Line Voltage Approved Dimmers

Leviton		Lutron	
VPI06-1LZ	DZ6HD	SCL-153PR	CTCL-153PDH
TTI06-1LZ	6674	DVCL-153PR	PD-6WCL
IPL06	6672	DVWCL-153PH	PD-5NE-WH



3030 Corporate Grove Dr.
 Hudsonville, MI 49426
 Phone: 616.396.1355
itc-us.com



REV: 032624

Product Details: Standard Non-Stock

Part #	694EM3036-KKSO00B	694EM3636-KKSO00B	694EM4236-KKSO00B	694EM4836-KKSO00B
Dimensions	30"W x 36"H x 1.7"D	36"W x 36"H x 1.7"D	42"W x 36"H x 1.7"D	48"W x 36"H x 1.7"D
Housing	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Lens	Glass	Glass	Glass	Glass
Wattage	34W	38W	41W	45W
Voltage	24V DC	24V DC	24V DC	24V DC
Current	1.4A	1.6A	1.7A	1.9A
Lumens	2825LM @ 3500K	3170LM @ 3500K	3500LM @ 3500K	3825LM @ 3500K
Kelvin	3000K, 3500K or 4000K	3000K, 3500K or 4000K	3000K, 3500K or 4000K	3000K, 3500K or 4000K

Part #	694EM5436-KKSO00B	694EM6036-KKSO00B	694EM7236-KKSO00B
Dimensions	54"W x 36"H x 1.7"D	60"W x 36"H x 1.7"D	72"W x 36"H x 1.7"D
Housing	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Lens	Glass	Glass	Glass
Wattage	49W	52W	60W
Voltage	24V DC	24V DC	24V DC
Current	2A	2.2A	2.5A
Lumens	4170LM @ 3500K	4500LM @ 3500K	5170LM @ 3500K
Kelvin	3000K, 3500K or 4000K	3000K, 3500K or 4000K	3000K, 3500K or 4000K

Notes:

1. Lumens per watt based on light source
2. Standard non-stock mirrors subject to 90 day lead time
3. Custom mirrors available upon request, subject to a 50 piece minimum, 50% deposit and 90 day lead time following approved drawings
4. Mirrors must be shipped LTL and cannot be shipped via FedEx or UPS
5. Warranty: 10-year frame and structure - 7-year glass, power supply and LEDs

