

Contour™ Classic

Integrated LED Backlit Mirror



Features

- Rounded corners for a modern aesthetic
- Outer frame provides added protection
- Outer perimeter etching ensures even illumination across mirror surface
- Two power supply options available, including 0-10V and line voltage dimming
- Copper-free backing for greater scratch and corrosion resistance
- Various size and frame color options available (contact sales for stock)

Specification Guide

Sample Part #: 694FM2436-30SO001




Base Part #	Size	Color Temp.	Output/Frame Color
694FM	2436 - 24"W x 36"L 4236 - 42"W x 36"L	30 - 3000K	SO001 - Black

*Power Supplies are ordered separately

Product Details

Part #'s	694FM2436-KKSO001	694FM4236-KKSO001	690010.121 - 0-10V Dimming 690010.143 - Line Voltage
Dimensions	24"W x 36"H x 1.7"D	42"W x 36"H x 1.7"D	13"L x 1.25"W x 1.7"D
Housing	Anodized Aluminum	Anodized Aluminum	Aluminum
Lens	Glass	Glass	N/A
Wattage	32W	44W	96W
Voltage	24V DC	24V DC	120 - 277V AC
Current	1.4A	1.9A	Max 4A
Lumens	2700LM @ 3500K	3600LM @ 3500K	N/A
Kelvin	3000K	3000K	N/A
Power Factor	N/A	N/A	0.94 @ 120V AC
Frequency	N/A	N/A	50 - 60Hz



Line Voltage Approved Dimmers

Leviton		Lutron	
VPI06-1LZ	DZ6HD	SCL-153PR	CTCL-153PDH
TTI06-1LZ	6674	DVCL-153PR	PD-6WCL
IPL06	6672	DVWCL-153PH	PD-5NE-WH



3030 Corporate Grove Dr.
Hudsonville, MI 49426
Phone: 616.396.1355
itc-us.com

REV: 032624

Product Details: Standard Non-Stock

Part #	694FM3036-KKSO001	694FM3636-KKSO001	694FM4836-KKSO001
Dimensions	30"W x 36"H x 1.7"D	36"W x 36"H x 1.7"D	48"W x 36"H x 1.7"D
Housing	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Lens	Glass	Glass	Glass
Wattage	36W	40W	48W
Voltage	24V DC	24V DC	24V DC
Current	1.5A	1.7A	2A
Lumens	3005LM @ 3500K	3290LM @ 3500K	3905LM @ 3500K
Kelvin	3000K, 3500K or 4000K	3000K, 3500K or 4000K	3000K, 3500K or 4000K

Part #	694FM5436-KKSO001	694FM6036-KKSO001	694FM7236-KKSO001
Dimensions	54"W x 36"H x 1.7"D	60"W x 36"H x 1.7"D	72"W x 36"H x 1.7"D
Housing	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Lens	Glass	Glass	Glass
Wattage	52W	56W	64W
Voltage	24V DC	24V DC	24V DC
Current	2.2A	2.4A	2.7A
Lumens	4190LM @ 3500K	4500LM @ 3500K	5090LM @ 3500K
Kelvin	3000K, 3500K or 4000K	3000K, 3500K or 4000K	3000K, 3500K or 4000K

- Notes:**
1. Lumens per watt based on light source
 2. Standard non-stock mirrors subject to 90 day lead time
 3. Custom mirrors available upon request, subject to a 50 piece minimum, 50% deposit and 90 day lead time following approved drawings
 4. Mirrors must be shipped LTL and cannot be shipped via FedEx or UPS
 5. Warranty: 10-year frame and structure - 7-year glass, power supply and LEDs

