

Enhance™ Classic

Integrated LED Backlit Mirror



Features

- Copper-free backing for greater scratch and corrosion resistance
- 3x magnification with integrated magnifying mirror
- Two dimmable power supplies available for either 0-10V or line voltage dimming
- Bright, even illumination prevents shadows
- Various size and color options (contact sales for stock)

Specification Guide

Sample Part #: 694MM2436-30SO00B


Base Part #
 Size
 Color Temperature
 Output

Base Part #	Size	Color Temp.	Output
694MM	2436 - 24"W x 36"L	30 - 3000K	SO00B - Standard

*Power Supplies are ordered separately

Product Details

Part #'s	694MM2436-KKSO00B	690010.121 - 0-10V Dimming 690010.143 - Line Voltage
Dimensions	24"W x 36"H x 1.7"D	13"L x 1.25"W x 1.7"D
Housing	Anodized Aluminum	Aluminum
Lens	Glass	N/A
Wattage	34W	96W
Voltage	24V DC	120 - 277V AC
Current	1.5A	Max 4A
Lumens	2800LM @ 3500K	N/A
Kelvin	3000K	N/A
Power Factor	N/A	0.94 @ 120V AC
Frequency	N/A	50 - 60Hz



Line Voltage Approved Dimmers

Leviton		Lutron	
VPI06-1LZ	DZ6HD	SCL-153PR	CTCL-153PDH
TTI06-1LZ	6674	DVCL-153PR	PD-6WCL
IPL06	6672	DVVCL-153PH	PD-5NE-WH



3030 Corporate Grove Dr.
 Hudsonville, MI 49426
 Phone: 616.396.1355
 itc-us.com

REV: 032624

Product Details: Standard Non-Stock

Part #	694MM3036-KKSO00B	694MM3636-KKSO00B	694MM4236-KKSO00B	694MM4836-KKSO00B
Dimensions	30"W x 36"H x 1.7"D	36"W x 36"H x 1.7"D	42"W x 36"H x 1.7"D	48"W x 36"H x 1.7"D
Housing	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Lens	Glass	Glass	Glass	Glass
Wattage	44W	48W	52W	55W
Voltage	24V DC	24V DC	24V DC	24V DC
Current	1.9A	2A	2.2A	2.3A
Lumens	3165LM @ 3500K	3530LM @ 3500K	3900LM @ 3500K	4265LM @ 3500K
Kelvin	3000K, 3500K or 4000K	3000K, 3500K or 4000K	3000K, 3500K or 4000K	3000K, 3500K or 4000K

Part #	694MM5436-KKSO00B	694MM6036-KKSO00B	694MM7236-KKSO00B
Dimensions	54"W x 36"H x 1.7"D	60"W x 36"H x 1.7"D	72"W x 36"H x 1.7"D
Housing	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Lens	Glass	Glass	Glass
Wattage	59W	62W	69W
Voltage	24V DC	24V DC	24V DC
Current	2.5A	2.6A	2.9A
Lumens	4630LM @ 3500K	5000LM @ 3500K	5730LM @ 3500K
Kelvin	3000K, 3500K or 4000K	3000K, 3500K or 4000K	3000K, 3500K or 4000K

- Notes:**
1. Lumens per watt based on light source
 2. Standard non-stock mirrors subject to 90 day lead time
 3. Custom mirrors available upon request, subject to a 50 piece minimum, 50% deposit and 90 day lead time following approved drawings
 4. Mirrors must be shipped LTL and cannot be shipped via FedEx or UPS
 5. Warranty: 10-year frame and structure - 7-year glass, power supply and LEDs

