Astra™ LED Tape Light



Specification Guide

Base Part #: TPB12RW-50012-10-G Base Part # Voltage Color Temperature Light Length Wire Length Special Character

Light Wire Special Base Part # Voltage Color Temp. Character Length Length 31 - 3100K 63 - 6300K BL - Blue RD - Red 02 - Amber/ White TPE - Single 03 - Blue/ 10 - Single, Dual Color White 500 - 197" Color/RGB & 12 - 12V 04 - Red/ (16.4') 12 - 12" Addressable TPB - RGB/ 10-G - RGBW White RGBW/ 05 - Red/Blue ARGR 07 - Red/ Amber 06 - RGB AM - Amber RW - RGBW AR - Addressable


Note: Light cannot be field cut, contact sales for information on custom lengths


Features

- RGB(W) chips provide an endless amount of color combinations and provides the ability to change colors instantly with a simple controller interface (purchased separately)
- Flexibility allows for installation in curved applications as well as straight mount applications
- Easy to install adhesive backing for quick and durable installation (with 3M 9495LE high performance non-woven double coated tape)
- RGB(W) and addressable work with ITC's VersiControl smart system and phone app

Product Details

	I	1	
	Single Color	RGB	RGBW
Voltage	10-14V DC		
Wattage	1.1 W/Ft	3 W/Ft Address: 2.6 W/Ft	3.6 W/Ft
Current	0.12 A/Ft	0.2 A/Ft Address: 0.2 A/Ft	0.27 A/Ft
Lumens	75 LM/Ft	82 LM/Ft Address: 90 LM/Ft	130 LM/Ft
Color Temp.	3000K, 6300K, Blue, Amber or Red	RGB	RGBW
IP Rating	IP64		
UV Stable	Yes		
Wire Gauge	18 AWG	22 AWG Address: 18 AWG	24 AWG









Accessory Specification

Description	Part #		
8MM Single Color Channel			
Black Plastic Straight Mount Track Without Tape	TPB-1		
Clear Plastic Straight Mount Track Without Tape	TPB-2		
10MM RGB/RGBW Channel			
Black Plastic Straight Mount Track Without Tape	TPB10-LS		
Black Plastic Straight Mount Track With Tape	TPB10-LT		
White Plastic Straight Mount Track Without Tape	TPB10-KS		
White Plastic Straight Mount Track With Tape	TPB10-KT		

