Piper™ 2.0 Front Cap Flex Light





Features

- Co-extruded silicone housing withstands wind and water spray, such as that experienced on the front of a vehicle
- · Available in bulk rolls or custom cut lengths
- · Available in warm white, cool white, blue, red or green
- Includes easy to install adhesive backing for quick and durable installation
- Plastic mounting channels available with or without 3M 9495LE adhesive backing
- · IP64 rated for water resistant applications

Product Details

| Voltage | 10-14V DC | | | | | |
|-------------|---|--|--|--|--|--|
| Wattage | 1.1W/Ft | | | | | |
| Current | 0.12A/Ft | | | | | |
| Lumens | 80LM/Ft | | | | | |
| Color Temp. | 3000K, 3500K, 4000K, 6300K, Blue, Red or Green | | | | | |
| IP Rating | IP64 | | | | | |
| UV Stable | Yes | | | | | |
| Wire Gauge | 18 AWG | | | | | |

Specification Guide

| Sample Part #: 1 | ΓPQ | 123 | O-' | 700 |)12- | -8 |
|---|-----|-----------|-----------|------------|--------------|----|
| | : | | | : | : | : |
| Base Part # · · · · · · · · · · · · · · · · · · | | | | | | : |
| Voltage ····· | | : | | ÷ | | |
| Color Temperature | | | | ÷ | | |
| Light Length | | | | : | ÷ | i |
| Wire Length | | | | | ! | |
| Light Width ····· | | • • • • • | • • • • • | | | .: |

| Base Part # | Voltage | Color Temp. | Light Length | Wire Length | Light Width |
|-------------|----------|---|--------------|----------------|-------------|
| TPQ | 12 - 12V | 30 - 3000K 35 - 3500K 40 - 4000K 63 - 6300K BL - Blue RD - Red GR - Green | 700 - 700cm | 12 - 12" | 8 - 8mm |

Note: Light cannot be field cut, contact sales for information on custom lengths

TPB-1:72" Black Palstic Screw Mount Channel

TPB-2:72" Clear Plastic Adhesive Mount Channel



itc-us.com